

CROWN

2 MHz X-Y OSCILLOSCOPE



TECHNICAL SPECIFICATIONS :

VERTICAL CHANNEL :

Sensitivity	:	20 mV P/P cm. at 1KHz
Frequency Response	:	10 Hz to 2MHz (-3db)
Input Impedance	:	1M Ω shunted by 40 PF (approx)
Attenuator	:	3 steps of 1 : 1 , 1 : 10 & 1 : 100 with in between continuously variable control

HORIZONTAL CHANNEL :

Sensitivity	:	50 mV P/P per cm at 1KHz
Frequency Response	:	10 Hz to 1MHz (-3db)
Input Impedance	:	1M Ω shunted by 40 PF (approx)
Attenuator	:	3 steps of 1 : 1 , 1 : 10 & 1 : 100 with in between continuously variable control

X - Y OPERATION :

Band Width	:	10 Hz to 1MHz
------------	---	---------------

SWEEP FREQUENCY :

Frequency	:	10 Hz to 100KHz in 4 range with Vernier
Synchronization	:	1. Internal 2. External 3. Line i.e. 50 Hz
Display	:	130 mm Diameter CRT , Display area 10 x 10 Cm.
Power Requirement	:	230VAC \pm 10%

=====
For Further Details Please Contact :

CROWN ELECTRONIC SYSTEMS

(AN ISO 9001: 2000 certified company)

**69/2A , IInd FLOOR , NAJAFGARH ROAD INDL. AREA , NEAR MOTI NAGAR CROSSING
NEW DELHI-110015**

Visit us at: www.Crownelectronicssystem.com

E-mail: crownelectronicssystem@yahoo.com

PH : 011- 64508649-50 , 25995324 , Tele Fax : 011- 45013465

CROWN OFFERS YOU A WIDE RANGE OF: OSCILLOSCOPE , AUDIO OSCILLATOR , FUNCTION GENERATOR , DC REGULATED POWER SUPPLY, DIGITAL FREQUENCY COUNTER/ MILLI OHM METER/ pH METER/ DPM,s FOR V,A, Hz., AND WATT, VTVM, LCR METER, HIGH VOLTAGE BREAK DOWN TESTER, AF POWER OUTPUT METER, AND ALL OTHER INSTRUMENTS, COMPONENTS AND ACCESSORIES, FOR ELECTRONICS AND ELECTRICAL LAB.